



水務署

Water Supplies Department

香港灣仔告士打道七號入境事務大樓

Immigration Tower, 7 Gloucester Road, Hong Kong

電子郵件

e-mail

wsdinfo@wsd.gov.hk

電話

Telephone

2829 4355

圖文傳真

Facsimile

2824 0578

檔號

Reference

(2) in WSD 3321/17 Pt.1 T/J(994)

21 August 2017

Approval of "ARMITAGE SHANKS" Combination Tap Assemblies

Your letter ref. L17-219 dated 17 July 2017 refers.

It is noted that the fittings described below have been accepted by the United Kingdom Water Regulations Advisory Scheme (WRAS) to have complied with the requirements of the United Kingdom Water Supply (Water Fittings) Regulations / Scottish Water Byelaws when correctly installed.

Name of Manufacturer: Ideal Standard Productions - GmbH

Country of Origin: UK

Brand: Armitage Shanks

Details of Fittings: Range of wall mounted two hole, single outlet (fixed) combination tap assemblies (chromium plated brass) incorporating a solenoid controlling the flow via an infrared sensor. Temperature is controlled via a thermostatic mixing valve. The products are supplied with two in-line 'Y' pattern strainers incorporating an isolation valve, as well as a single check valve cartridge (suitable for backflow protection against fluid category 2) for installation on each inlet, and metal backnuts. The A6684AA has a demountable spout.

Maximum working pressure 6.0 bar. Maximum operating temperature 60°C.

Model: A6684AA & A6737AA

Size: 15mm compression

Marking: *Avantage Shanks* on operating member

WRAS Approval Number: 1705015

Installation Requirements: R001, R040

Expiry Date: 31 May 2022

In view of the acceptance by WRAS, this Authority has no objection to the use of the said fittings in fresh water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following installation requirements –

“Installation shall comply with the ‘Installation Requirements & Notes’ of the WRAS’s approval letter concerned.”

“The cold water supply to the fittings shall be drawn from the same source that supplies the hot water apparatus so as to provide a balanced pressure and to obviate the risk of scalding in the event of a restriction or failure in the water supply.”

“A stop cock or gate valve must be installed at the upstream of the fittings for manual isolation of water supply.” AND

“The main voltage operated sensor valve should comply with the electricity safety regulation for applications in bathroom, toilet etc.”

A condition of this acceptance is that the fittings to be installed should be replicas of the samples certified by WRAS and no modification should be made to the fittings. This acceptance may be withdrawn at any time if the standard of the fittings installed fails to meet that of the approved samples or if the fittings are found to be unsuitable for use in fresh water plumbing systems.

This acceptance is only applicable to the main body of the fittings, unless other specified.

For the use of the fittings in any project, the Acceptance Reference Number at the bottom of this letter must be quoted as a means of identification of acceptance of the fittings by this Authority.

Should you have any enquiries, please contact our Engineer Mr Terry KUNG at tel. no. 2294 2656.

Yours faithfully,



(Roger WONG)
for Water Authority

c.c. WSD 3321/1/82] - without catalogue
 ME/MC] - with soft copy only



A6684AA



A6737AA