



水務署
Water Supplies Department

總部 Headquarters

香港灣仔告士打道七號入境事務大樓 48 樓

48/F, Immigration Tower, 7 Gloucester Road, Wan Chai, Hong Kong

本署檔號 : (6) in WSD 3321/19 T/J(1086/2019)
Our ref.
來函檔號 :
Your ref.

電話 :
Tel.
傳真 : 2824 0578
Fax.

18 February 2020

**Approval of “JETOM” Flexible Hoses
(General Acceptance No. B20200011)**

Your letters dated 14 November 2019, 17 December 2019 and 14 January 2020 refer.

It is noted that the fittings described below have been accepted by the United Kingdom Water Regulations Advisory Scheme (WRAS) to have complied with the requirements of the United Kingdom Water Supply (Water Fittings) Regulations / Scottish Water Byelaws when correctly installed. This Authority accepts that the fittings described below based on the WRAS certificate comply with, and their use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer: Quanzhou Jetom Hose Industry Co Ltd

Country of Origin: the Mainland of China

Brand: Jetom

Details of Fitting: Range of stainless steel braided EPDM lined flexible hoses with EPDM washers and ‘O’-rings. Maximum working pressure 10.0 bar. Maximum operating temperature 85°C.

Model:	1. Bore diameter DN7: H5MAJ-XXX101C-1, H5MAL-XXX101C-1, H5MAM-XXX101C-1, H5MAN-XXX101C-1, H5MAP-XXX101C-1, H5MAQ-XXX101C-1, H5MAS-XXX101C-1, H5MAT-XXX101C-1, H5MAU-XXX101C-1 2. Bore diameter DN8: H5NAJ-XXX101C-1, H5NAL-XXX101C-1, H5NAM-XXX101C-1, H5NAN-XXX101C-1, H5NAP-XXX101C-1, H5NAQ-XXX101C-1, H5NAS-XXX101C-1, H5NAT-XXX101C-1, H5NAU-XXX101C-1 3. Bore diameter DN10: H5PAJ-XXX101C-1, H5PAL-XXX101C-1, H5PAM-XXX101C-1, H5PAN-XXX101C-1, H5PAP-XXX101C-1, H5PAQ-XXX101C-1, H5PAS-XXX101C-1, H5PAT-XXX101C-1, H5PAU-XXX101C-1 (Where XXX denotes the length of the hose from 30cm - 200cm, e.g. 050 = 50cm, 200 = 200cm)
Size:	$\frac{3}{8}$ ", $\frac{1}{2}$ ", M10, M12, M15
Body Markings:	Jetom, WRAS and date of manufacture (YYYY) on crimped connector
WRAS Approval Number:	1801052
Installation Requirements:	R001
Expiry Date:	31 January 2023

In view of the acceptance by WRAS, this Authority has no objection to the use of the said fittings in fresh water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following installation requirements –

“Installation shall comply with the ‘Installation Requirements & Notes’ of the WRAS’s approval letter concerned.” AND

“The inlet flexible hose is applied for the water tap or mixer connection only and installed in the fresh water plumbing systems.”

A condition of this acceptance is that the fittings to be installed should be replicas of the samples certified by WRAS and no modification should be made to the fittings. This acceptance may be withdrawn at any time if the standard of the fittings installed fails to meet that of the approved samples or if the fittings are found to be unsuitable for use in fresh water plumbing systems.

For the use of the fittings in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fittings by this Authority.

Should you have any enquiries, please contact our Engineer Mr. Terry KUNG at tel. no. 3583 4086.

Yours faithfully,



(CHAN Chung-kun)

for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82] - without catalogue
 ME/MC] - with soft copy only



H5MAJ-XXX101C-1 / H5MAP-XXX101C-1 / H5MAQ-XX101C-1 /
H5NAJ-XXX101C-1 / H5NAP-XXX101C-1 / H5NAQ-XXX101C-1 /
H5PAJ-XXX101C-1 / H5PAP-XXX101C-1 / H5PAO-XXX101C-1



H5MAL-XXX101C-1 / H5MAM-XXX101C-1 / H5MAS-XXX101C-1 /
H5MAT-XXX101C-1 / H5NAL-XXX101C-1 / H5NAM-XXX101C-1 /
H5NAS-XXX101C-1 / H5NAT-XXX101C-1 / H5PAL-XXX101C-1 /
H5PAM-XXX101C-1 / H5PAS-XXX101C-1 / H5PAT-XXX101C-1



H5MAN-XXX101C-1 / HSMAU-XXX101C-1 /
H5NAN-XXX101C-1 / HSNAU-XXX101C-1 /
H5PAN-XXX101C-1 HSPAU-XXX101C-1