



水務署
Water Supplies Department

總部 Headquarters

香港灣仔告士打道七號入境事務大樓 48 樓

48/F, Immigration Tower, 7 Gloucester Road, Wan Chai, Hong Kong

本署檔號 : (4) in WSD 3321/2022 T/J(1384/2022)
Our ref.
來函檔號 :
Your ref.

電話 :
Tel.
傳真 : 2824 0578
Fax.

6 February 2023

**Approval of “F.Q.R.” Flexible Hoses
(General Acceptance No. B20230002)**

Your letters dated 28 October 2022 and 9 January 2023 refer.

It is noted that the fittings described below have been accepted by the United Kingdom Water Regulations Advisory Scheme (WRAS) to have complied with the requirements of the United Kingdom Water Supply (Water Fittings) Regulations / Scottish Water Byelaws when correctly installed. This Authority accepts that the fittings described below based on the WRAS certificate comply with, and their use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer: FQR Frattini Srl

Country of Origin: Italy

Brand: F.Q.R.

Details of Fittings: Stainless steel or nylon braided inlet flexible hose for tap/mixer

Model and Size:

Model	Bore Size	Size of End Connections
DN6K, DN6KL, DN6KZ, P6K, P6KL, P6KZ	DN6	10x1, 11x1, 12x1, 15x1, 14x1, F3/8, F1/2, F15x1, F14x1, F9/16, M3/8, M1/2, NPB Ø15, Ø15 c.o, F3/8 c/curva, F1/2 c/curva, F1/2 conical
DN8K, DN8KL, DN8KZ, DPV8K, DPV8KL, DPV8KZ, P9K, P9KL, P9KZ	DN8	10x1, 11x1, 12x1, 15x1, 14x1, F3/8, F1/2, F3/4, F15x1, F14x1, F9/16; M3/8, M1/2, NPB Ø15, Ø15 c.o., F3/8 c/curva, F1/2 c/curva; F1/2 conical
DN10K, DN10KL, DN10KZ	DN10	12x1, F3/8, F1/2, F3/4, M3/8, M1/2, NPB Ø15, Ø15 c.o., F3/8 c/curva, F1/2 c/curva, F1/2 conical
DN13K, DN13KL, DN13KZ	DN13	F1/2, F3/4, M1/2, M3/4, F1/2 c/curva

Body Markings: FQR, date of manufacture (YY) & WRAS on ferrule

WRAS Approval Number: 2210345
(Appendix A of WRAS approval letter refers)

Installation Requirements: R001, R008

Expiry Date: 31 October 2027

In view of the acceptance by WRAS, this Authority has no objection to the use of the said fittings in fresh water plumbing systems subject to full adherence to Waterworks installation requirements. In particular, you are required to draw your customers' attention to the following installation requirements –

“Installation shall comply with the ‘Installation Requirements & Notes’ of the WRAS’s approval letter concerned.” AND


“The inlet flexible hoses are applied for the water tap or mixer connection only and installed in the fresh water plumbing systems.”

A condition of this acceptance is that the fittings to be installed should be replicas of the samples certified by WRAS and no modification should be made to the fittings. This acceptance may be withdrawn at any time if the standard of the fittings installed fails to meet that of the approved samples or if the fittings are found to be unsuitable for use in fresh water plumbing systems.

For the use of the fittings in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fittings by this Authority.

Should you have any enquiries, please contact our Engineer Ms Winnie LO at tel. no. 3583 4086.

Yours faithfully,



(YAU Hau Yin)
for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82] - without catalogue
 ME/MC] - with soft copy only



DN6K / DN6KL / DN6KZ / DN8K / DN8KL / DN8KZ / DN10K /
DN10KL / DN10KZ / DN13K / DN13KL / DN13KZ



DPV8K / DPV8KL / DPV8KZ



P6K / P6KL / P6KZ / P9K / P9KL / P9KZ