



水務署
Water Supplies Department

總部 Headquarters

香港灣仔告士打道七號入境事務大樓 48 樓

48/F, Immigration Tower, 7 Gloucester Road, Wan Chai, Hong Kong

本署檔號 : (6) in WSD 3321/2024 T/J(567/2024)
Our ref.
來函檔號 :
Your ref.

電話 :
Tel.
傳真 : 2824 0578
Fax.

10 September 2024

**Approval of “KURIMOTO” Ductile Iron Fittings
(General Acceptance No. C20240626)**

Your letters ref. 623/2024, 774/2024 and 825/2024 dated 11 June 2024, 30 July 2024 and 19 August 2024 respectively refer.

Having considered the test reports ref. PMA04216C and PMA04217B both issued on 24 July 2024 and ref. PMA04218B issued on 15 March 2021 by ETS-Testconsult Ltd. and WRAS certificate, this Authority accepts that the fittings described below comply with, and their use when correctly installed does not contravene, the Waterworks Ordinance and Regulations.

Name of Manufacturer: Kurimoto Ltd

Country of Origin: the Mainland of China

Brand: Kurimoto

Details of Fittings: Ductile iron fittings with internal cement mortar lining under WRAS approval no. 2207526

Description	Size (mm)
Double Flanged 90° Bend (PN16)	150, 200, 250, 300
Double Flanged 45° Bend (PN16)	150, 200, 250, 300
Double Flanged 90° Bend (PN25)	80, 100, 150

Description	Size (mm)
Double Flanged 45° Bend (PN25)	80, 100, 150, 200
Double Socket 90° Bend	80, 100, 150, 200, 250, 300
Double Socket 45° Bend	80, 100, 150, 200, 250, 300
Double Socket 22.5° Bend	80, 100, 150, 200, 250, 300
Double Socket 11.25° Bend	80, 100, 150, 200, 250, 300
All Flanged Tee (PN16)	80x80x50, 80x80x80, 100x100x80, 100x100x100, 150x150x80, 150x150x100, 150x150x150, 200x200x80, 200x200x100, 200x200x150, 200x200x200, 250x250x250, 300x300x300
All Flanged Tee (PN25)	80x80x80, 100x100x100, 150x150x150
All Socket Tee	250x250x250, 300x300x300
Double Flanged Taper (PN16)	80x50, 100x80, 150x80, 150x100, 200x150, 250x200, 300x250
Double Socket Taper	100x80, 150x100, 200x150, 250x200, 300x250

Body Markings:

For Double Flanged Bend (PN16):

BS EN 545 DI K12 PN16 size x angle **X**

For Double Flanged Bend (PN25):

BS EN 545 DI K12 PN25 size x angle **X**

For Double Socket Bend:

BS EN 545 DI K12 size x angle **X**

For All Flanged Tee (PN16) and Double Flanged Taper:

BS EN 545 DI K12 PN16 size x size **X**

For All Flanged Tee (PN25):

BS EN 545 DI K12 PN25 size x size **X**

For All Socket Tee and Double Socket Taper:

BS EN 545 DI K12 size x size **X****Expiry Date:**

19 October 2025

This Authority hereby permits the use of the above fittings in fresh water plumbing systems, flushing water plumbing systems and fresh water fire services systems subject to full adherence to Waterworks installation requirements.

A condition of this acceptance is that the fittings to be installed shall be replicas of the samples as certified by the testing agent mentioned above and without modifications. This acceptance may be withdrawn at any time if the standard of the fittings installed fails to meet that of the approved samples or if the fittings are found to be unsuitable for use in the water supply systems mentioned above.

For the use of the fittings in any project, the General Acceptance Number of this letter must be quoted as a means of identification of acceptance of the fittings by this Authority.

Should you have any enquiries, please contact our Engineer Mr Albert CHOW at tel. no. 3583 4086.

Yours faithfully,



(Terry KUNG)

for Director of Water Supplies

Encl.

c.c. WSD 3321/1/82] - without catalogue
 ME/MC] - with soft copy only



Double Flanged 90° Bend (PN16)



Double Flanged 45° Bend (PN16)



Double Flanged 90° Bend (PN25)



Double Flanged 45° Bend (PN25)



Double Socket 90° Bend



Double Socket 45° Bend



Double Socket 22.5° Bend



Double Socket 11.25° Bend



All Flanged Tee (PN16)



All Flanged Tee (PN25)



All Socket Tee



Double Flanged Taper (PN16)



Double Socket Taper